

▼ Shown: HC-7206



## Thermo-Plastic Safety Hoses (700-Series)

- For demanding applications, featuring a 4:1 safety factor
- Maximum working pressure of 700 bar
- Outside jacket is polyurethane, to provide maximum abrasion resistance
- Exhibits low volumetric expansion under pressure to enhance overall system efficiency
- Crimped-on rubber strain relief for improved life and durability on all models.

▼ To prevent back pressure and to increase cylinder retraction speed, when using long hoses with single-acting cylinders, the Enerpac HC-7300-Series of hoses with increased internal diameter is the best choice.



## Safety and Quality



To ensure the integrity of your system, specify only Enerpac hydraulic hoses.

### WARNING !

- Do not exceed 700 bar maximum pressure.
- Do not handle hoses which are under pressure.

More safety instructions in our 'Yellow pages'.

Page: **246**

### ▼ Hose End Couplings

1/4" NPTF	
3/8" NPTF	
A-604	
A-630	
AH-604	
AH-630	
C-604	
CH-604	

# High Pressure Hydraulic Hoses

## H700 Series



Inside Diameter:

**6,4 - 9,7 mm**

Length:

**0,6 - 15 m**

Maximum Operating Pressure:

**700 bar**

Internal Diameter (mm)	Hose End Assemblies and Couplers *		Hose Length (m)	Model Number	Weight (kg)		
	End one	End two					
6,4	1/4" NPTF		-	-	-		
			-	-	-		
		A-630	1,8	HB-7206QB	1,1		
			-	-	-		
		CH-604	1,8	HC-7206Q	1,0		
	3/8" NPTF		3/8" NPTF	0,6	H-7202	0,5	
				0,9	H-7203	0,7	
				1,8	H-7206	0,9	
				3,0	H-7210	1,4	
				6,1	H-7220	2,8	
				9,1	H-7230	4,5	
				15	H-7250	7,0	
					-	-	-
		A-604	1,8	HA-7206B	1,1		
			-	-	-		
		AH-604		3/8" NPTF	-	-	-
					1,8	HA-7206	1,0
					3,0	HA-7210	1,5
					1,8	HB-7206	1,0
					0,9	HC-7203B	1,0
					1,8	HC-7206B	1,3
	C-604		3/8" NPTF	3,0	HC-7210B	1,8	
				0,9	HC-7203	0,8	
				1,8	HC-7206	1,0	
CH-604		3/8" NPTF	3,0	HC-7210	1,5		
			6,1	HC-7220	2,9		
			1,8	HC-7206C	1,1		
CH-604	CH-604	3/8" NPTF	15	HC-7250C	7,0		
			1,8	H-7306	1,6		
9,7	3/8" NPTF	3/8" NPTF	-	-	-		
			3,0	H-7310	2,4		
			6,1	H-7320	4,5		
			9,1	H-7330	7,3		
			15	H-7350	11,5		
		CH-604	CH-604	1,8	HC-7306	1,7	
				3,0	HC-7310	2,5	
				6,1	HC-7320	5,1	

\* For technical information on couplers see next page.



### Torque Wrench Hoses

Use Enerpac twin safety hoses with double-acting wrenches to ensure the integrity of your hydraulic system.

Page: 200



### Fittings

For additional fittings see the fitting page of the System Components section.

Page: 121

### Hose Oil Capacity

When using greater hose lengths, it is sometimes necessary to fill the pump reservoir after filling the hoses. To determine the hose oil capacity, use the following:

For 6,4 mm inside diameter hoses:  
Capacity (cm<sup>3</sup>) = 32,1699 x Length (m)

For 9,7 mm inside diameter hoses:  
Capacity (cm<sup>3</sup>) = 73,8981 x Length (m)